TECHNICAL SPECIFICATIONS

WIDTH: 19" and 25" DEPTH: 600mm, 700mm, 800mm

Freestanding Cabinets

ITEM	DESCRIPTION	RAW MATERIAL
ALUMINIUM FRAME	BUILT OF 4 ALUMINIUM PROFILES	ALUMINIUM 6063
BOTTOM BASE	 INCLUDING: OPENINGS FOR CABLES ACCESS HOLES FOR FEET ASSEMBLY "OMEGA" PROFILE FOR GROUNDING KIT MOUNTING 	C.R.S. 2mm
TOP COVER	INCLUDING: OPENINGS FOR CABLE ENTRY FROM 3 DIRECTIONS OPENINGS FOR FANS	C.R.S. 2mm
"PAGODA" ROOF	FOR COVERING THE FANS	C.R.S. 1.25mm
FRONT DOOR	HARDENED SMOKED GLASS DOOR OR BLANK STEEL DOOR OR VENTED STEEL DOOR WITH LOCK	6mm HARDENED SMOKED GLASS or C.R.S. 1.25mm
REAR DOOR	BLANK STEEL OR VENTED STEEL , WITH LOCK	C.R.S. 1.25mm
SIDE PANELS	2 REMOVABLE SIDE PANELS WITH ABS GADGETS ALLOWING EASY ACCESS TO THE CABINET FROM BOTH SIDES	C.R.S. 1.25mm
MOUNTING ANGLES	4 ADJUSTABLE RACK MOUNTING ALUMINIUM OR GALVANIZED STEEL ANGLES FOR PROPER FIXING OF THE EQUIPMENT	or C.R.S. 2mm
INTERNAL DOORS FOR CABINETS 25"	FOR COVERING THE CABLES IN RIGHT AND LEFT SIDES	C.R.S. 1.25mm
FEET / CASTERS	STABILIZER FEET OR HEAVY DUTY CASTERS	
SHELVES	PERFORATED OR BLANK SHELVES, FIXED OR SLIDING	C.R.S. 1.25mm
DRAWERS	• 3U HEIGHT	C.R.S. 1.25mm
FINISHING	TEXTURED EPOXY ELECTROSTATIC POWDER PAINT 60 -90 MICRONS STANDARD COLOURS RAL 7032 / 7035 OR AS PER CLIENT'S REQUEST	